


# FIBER CLOSURE AND TERMINAL QUICK REFERENCE CHART



PRODUCT	DIMENSIONS		SPLICE CAPACITY	MID-SHEATH LENGTH	FEEDER / DROP DENSITY	ADAPTER PORTS	APPLICATION	ENVIRONMENTAL SEALING	TEST STANDARDS	GROUNDING	HARDENED OPTION	SPLITTERS	CABLE DIAMETER RANGE	PALLET QTY
 <b>Mini-G</b>	External Diameter	2.75"	N/A		1 Hardened	2, 4, or 8 Hardened	Underground Vault	Air/Water Tight Flood Proof	Telcordia GR771	None	Yes - Standard	PLC Type 60mm x 7mm x 4mm 1 Splitter Max		315
Height	6"	2, 4, or 8 Hardened			Pedestal		Core IP68		Aerial Pole					
 <b>G4N</b>	Internal Diameter	4"	24F (single stacked) 48F (double stacked) 96F (mass fusion)	5	1 Main Oval Port 4 Drop Ports	8 SC-APC	Underground Vault	Air/Water Tight Flood Proof	Telcordia GR771	Yes - dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9"	160
External Diameter	6.75"	Pedestal					Core IP68		Drop 0.062 - 0.562"					
 <b>G5NT</b>	Internal Diameter	5"	72F (single stacked) 144F (double stacked) 192F (mass fusion)	8	1 Main Oval Port 12 Drop Ports	16 SC-APC	Underground Vault	Air/Water Tight Flood Proof	Telcordia GR771	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9"	96
External Diameter	8.5"	Pedestal					Core IP68		Drop 0.062 - 0.562"					
 <b>G5NB</b>	Internal Diameter	5"	72F (single stacked) 144F (double stacked) 192F (mass fusion)	8	1 Main Oval Port 8 Drop Ports 1 Branch Port	16 SC-APC	Underground Vault	Air/Water Tight Flood Proof	Telcordia GR771	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9"	96
External Diameter	8.5"	Pedestal					Core IP68		Drop 0.062 - 0.562"				Branch 0.4 - 0.8"	
 <b>G6N</b>	Internal Diameter	6"	108F (single stacked) 216F (double stacked)	10	1 Main Oval Port 16 Drop Ports 1 Branch Port	16 SC-APC	Underground Vault	Air/Water Tight Flood Proof	Telcordia GR771	Yes - optional (requires 1 drop port)	Yes	PLC Type 60mm x 7mm x 4mm 6 Splitters Max	Main 0.188 - 0.9"	30
External Diameter	9.5"	Pedestal					Core IP68		Drop 0.062 - 0.562"				Branch 0.4 - 0.8"	
 <b>G9</b>	Internal Diameter	9"	144F (single stacked) 288F (double stacked)	14.5	1 Main Oval Port 16 Drop Ports 2 Branch Ports 1 Ground Port	16 SC-APC	Underground Vault	Air/Water Tight Flood Proof	Telcordia GR771	Yes - Optional bond strap and clips available	Yes		Main 0.188 - 0.9"	16
External Diameter	12"	Pedestal					Core IP68		Drop 0.062 - 0.562"				Branch 0.4 - 0.8"	
 <b>YJ</b>	External Width	16.0"	72F (single stacked) 144F (double stacked) 192F (mass fusion)	10	4 Main Cable Ports 16 Drop Ports	16 SC-APC	Aerial Strand	Dust Resistant Moisture Resistant	Telcordia GR771	Yes - Optional bond strap and clips available	Yes 8 ports max	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.1 - 0.9"	108
Height	8.75"	Pedestal					Core IP65		Drop 0.062 - 0.19"					
Depth	5.75"		IEC 61300	Branch 0.062 - 0.19"										